



Klemsan®

325109 AVK 4C

4mm², screw type, single deck 1 input 2 output terminal block, Insulating material PA, Grey

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
Dimensions	Width	6 mm
	Length	50.5 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	53.3 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	32 A
	Cross Section	4 mm ²
	Norm	EN60947-7-1
VDE Technical Data	Nominal Voltage	V ~
	Nominal Current	A
	Cross Section	mm ²
	VDE Norm	
UL / CSA Technical Data	Nominal Voltage	V ~
	Nominal Current	A
	Cross Section	
ATEX Technical Data	Nominal Voltage	V ~
	Nominal Current	A
	Cross Section	
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²
	Minimum fine Strand cross section	0.5 mm ²

Maximum fine strand cross section	6 mm ²
AWG Conductor Range	26-10
Connection Type	screw/vidalı
Insulation Stripping length	10 mm
Tightening torque	0.5 Nm



UL Sertifikası - UL Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

(ATEX) Potansiyel Patlayıcı atmosferlerde kullanılabilirlik belgesi - ATEX Certificate

Avrupa standartlarına uygunluk belgesi - CE Certificate

© 2018 Klemsan A.Ş.
www.klemsan.com