

Cable Ties

Weather Resttant Cable Ties

- ◆Material: Polyamide 6.6W/UV, 94V-2 certificated by UL. Acid & erosion control,insulate well and not easy to aging、 tensile strong.
- ◆Application temperature: -40℃—105℃
- ◆Installation temperature: -10℃—105℃
- ◆Features: Suitable for outdoor and indoor places exposed to ultraviolet radiation
- ◆Color: UV black



Item NO.	L		W(mm)	Max.Bundle DIA.(mm)	Tensile strength	
	Inch	mm			LBS	KGS
CHS-3×100HSW	4"	100	2.5	22	18	8
CHS-4×150HSW	6"	150	3.6	35	40	18
CHS-4×200HSW	8"	200	3.6	53	40	18
CHS-5×200HSW	8"	200	4.8	53	50	22
CHS-5×250HSW	10"	250	4.8	65	50	22
CHS-5×300HSW	11 5/8"	300	4.8	82	50	22
CHS-5×380HSW	15"	380	4.8	105	50	22
CHS-8×300HSW	11 5/8"	300	7.6	80	120	55
CHS-8×350HSW	13 3/4"	350	7.6	90	120	55
CHS-8×400HSW	15 3/4"	400	7.6	105	120	55
CHS-8×500HSW	19 11/16"	500	7.6	145	120	55



Cable Ties

High Temperture Resistant Cable Ties

- ◆Material: Polyamide46HR,94V-2 certificated by UL. Acid & erosion control,insulate well and not easy to aging、 tensile strong.
- ◆Application temperature: -40℃—120℃
- ◆Installation temperature: -10℃—120℃
- ◆Color: Natural



Item NO.	L		W(mm)	Max.Bundle DIA.(mm)	Tensile strength	
	Inch	mm			LBS	KGS
CHS-3 × 100HTR	4"	100	2.5	22	18	8
CHS-4 × 150HTR	6"	150	3.6	35	40	18
CHS-4 × 200HTR	8"	200	3.6	53	40	18
CHS-5 × 200HTR	8"	200	4.8	53	50	22
CHS-5 × 250HTR	10"	250	4.8	65	50	22
CHS-5 × 300HTR	11 5/8"	300	4.8	82	50	22
CHS-5 × 380HTR	15"	380	4.8	105	50	22
CHS-8 × 300HTR	11 5/8"	300	7.6	80	120	55
CHS-8 × 350HTR	13 3/4"	350	7.6	90	120	55
CHS-8 × 400HTR	15 3/4"	400	7.6	105	120	55
CHS-8 × 500HTR	19 11/16"	500	7.6	145	120	55

UL 94V-0 Cable Ties

- ◆Material: Polyamide 6.6, 94V-0 certificated by UL. Acid & erosion control,insulate well and not easy to aging、 tensile strong.
- ◆Application temperature: -40℃—85℃
- ◆Installation temperature: -10℃—85℃
- ◆Color: Milk White



Item NO.	L		W(mm)	Max.Bundle DIA.(mm)	Tensile strength	
	Inch	mm			LBS	KGS
CHS-3 × 100-V0	4"	100	2.5	22	18	8
CHS-4 × 150-V0	6"	150	3.6	35	40	18
CHS-4 × 200-V0	8"	200	3.6	53	40	18
CHS-5 × 200-V0	8"	200	4.8	53	50	22
CHS-5 × 250-V0	10"	250	4.8	65	50	22
CHS-5 × 300-V0	11 5/8"	300	4.8	82	50	22
CHS-5 × 380-V0	15"	380	4.8	105	50	22
CHS-8 × 300-V0	11 5/8"	300	7.6	80	120	55
CHS-8 × 350-V0	13 3/4"	350	7.6	90	120	55
CHS-8 × 400-V0	15 3/4"	400	7.6	105	120	55
CHS-8 × 500-V0	19 11/16"	500	7.6	145	120	55