



353 109 - ASK 3A ■ Grey



Technical Product Information

General Product Information

Insulating material	PA 66
Inflammability class acc. to UL 94	V2

Dimensions

Width	6 mm
Length	53.5 mm
Height (MR 32)	mm
Height (MR 35)	50.5 mm

TSE / CE Technical Data

Nominal Voltage	500 V ~
Nominal Current	16 A
Cross Section	4 mm ²
Norm	EN60947-7-1

VDE Technical Data

Nominal Voltage	V ~
Nominal Current	A
Cross Section	mm ²
VDE Norm	

UL / CSA Technical Data

Nominal Voltage	600 V ~
Nominal Current	16 A
Cross Section	26-10 mm ²

ATEX Technical Data

Nominal Voltage	V ~
Nominal Current	A
Cross Section	mm ²

Connection Data

Minimum solid strand cross section	0.5 mm ²
Maximum solid Strand cross section	6 mm ²
Minimum fine Strand cross section	1.5 mm ²
Maximum fine strand cross section	4 mm ²
AWG Conductor Range	26-10
Connection Type	screw/vidali
Insulation Stripping length	10 mm
Tightening torque	0.5 Nm

Mounting Rails



500 601 MR 35x7,5 (1 m.) 20



500 602 MR 35x7,5 20



500 603 MR 35x7,5 (2 m.) 20



500 604 MR 35x7,5 20



500 605 MR 35x7,5 (30 cm.) 20



500 606 MR 35x15 (1 m.) 20



500 607 MR 35x15 20

End Brackets



495 040
KD 3



495 050
KD 4



495 210
KD 7



495 219
KD 7

End Plates



450 050
NPP / ASK 3

Cross Connection

- 476 232 UK 4/2 - YBK 4 / ASK 3
- 476 233 UK 4/3 - YBK 4 / ASK 3
- 476 234 UK 4/4 - YBK 4 / ASK 3

Group Markings



496 110 GE



496 13A ME 1-2



496 300 ME3

